

Government of India
Ministry of Communications and Information Technology
Department of Information Technology, Standardisation Testing & Quality Certification Directorate
ELECTRONICS REGIONAL TEST LABORATORY (EAST)

TEST REPORT ON SOLAR PV MODULE

PAGE 01 OF 4

1.0 SCOPE


1.1 Service Request No. : TE/0078/07-12

1.2 Test Report No. : ERTL(E)/TES/D207/0007/08-12
Date : 23/08/2012

1.3 Requested by : **DEV INTERNATIONAL**
(Name & Address
of the organisation) 15.DR.THOTTAM
VALIYAMPALAYAM,KALAPATTI
COIMBATORE 641048
TAMILNADU

1.4 Description ,
Identification
of the item
to be tested

Item : SOLAR PV MODULE
Make : SREEDEV
Model : SD-3712
Sl.No. : 004
Qty. : 1

**1.4.1 Applicable Spec.of the item(s) tested:**

1.4.2 Characterisation and condition of the item

Characterisation : Not applicable /
Condition : Satisfactory /

1.5 Date of item receipt of item : 01/08/2012

1.6 Date of start of testing : 06/08/2012

1.6.1 Date of completion of testing : 21/08/2012

1.7 Location where testing performed : In house

1.8 Ambient condition during measurement : 25 +/- 1.5°C
70% RH. Max.

1.9 Spec. used for testing : STC PARAMETERS ONLY

1.9.1 Details of non-standard method followed (if any) : NIL



Certificate No. : T0002

Government of India
Ministry of Communications and Information Technology
Department of Information Technology, Standardisation Testing & Quality Certification Directorate
ELECTRONICS REGIONAL TEST LABORATORY (EAST)

TE/0078/07-12

J0007/TE/08-12

PAGE 3 OF 4



Panel :	SREEDEV
Type :	SD-3712
Panel no :	1
Serial no :	004
Date :	06-08-12
Mon. cell :	Poly+Th+filter - 10-0656-01
Sensitivity :	0.000077 mV
Act. Temp. :	23.1 °C
Result :	16

Temp. =	25.0 °C
Irrad. =	1.0 kW/m ²
Isc =	2.620 A
Voc =	22.585 V
Eff. =	19.2 %
FF =	77.9 %
MPP =	46.074 W
V@MPP =	18.930 V
I@MPP =	2.434 A
Rser. =	0.7 Ohm
Rsht =	646.8 Ohm
Ref Voltage	16.4 V
I Ref Voltage	2.584 A
P Ref Voltage	42.383 W

X Sin Bism

[Signature]